Diffusion gas exchanger - has lugs at corners of frames slotted, with distancing spacers in form of rectangular frames.

```
L20 ANSWER 94 OF 121 WPINDEX COPYRIGHT 2002 DERWENT INFORMATION LTD
                       WPINDEX
    1995-402504 [51]
DNN N1995-291322
DC
    074
    VOROBEV, E D
IN
     (VORO-I) VOROBEV E D
PΑ
CYC
                 C1 19950420 (199551)*
                                              10p
PΙ
    RU 2033579
ADT RU 2033579 C1 SU 1992-5045334 19920602
PRAI SU 1992-5045334 19920602
    1995-402504 [51]
                       WPINDEX
          2033579 C UPAB: 19951221
AΒ
```

The exchanger consists of a package of porous membranes (2) with distance spacers which together form two groups of mutually perpendicular uniflow channels with inlets and outlets located on opposite sides of the package. The distancing spacers are in the form of rectangular frames (1) which are equal in height.

Inside air from the work space is fed into one end of the exchanger and blown through it until it comes out at the other end to be returned to the work space. At the same time, outside air is blown through the diffuser at right angles to the **flow** of inside air before being returned to atmosphere. The membranes in the diffuser cleanse both the outside and inside air streams of undesirable gas components. In the case of the inside air, this entails removing carbonic gases and other gaseous components and replacing them with oxygen from the outside air and lodged in the pores of the membranes.

ADVANTAGE - Increase in the concentration and temperature gradients. Bul.No.11/20.4.95

Dwg.1/3